

ISUZU

ELF



SAFETY PLUS

SRS
AIRBAG

ASR
ANTI-SLIP REGULATOR

ABS
ANTI-LOCK BRAKING SYSTEM

EBD
ELECTRONIC BRAKE FORCE DISTRIBUTION

 **IMMOBILIZER**

AVAILABLE ON NMR 125 MODEL

4 WHEELER

GVW 4,800kg

GVW 5,100kg

NLR
PRO

NMR
125

5

YEARS WARRANTY
OR
300,000 km
WHICHEVER
COMES FIRST

EURO 4



FREE
SERVICE CAMPAIGN
 **ISUZU**

Product image for illustration purposes only. Actual product may vary.

SPECIFICATIONS

NLR PRO

NMR 125

MODEL CODE	NLR77UEE	NLR77UHE	NMR85UEH	NMR85UHH
Drive Train	4 x 2			
ENGINE				
Model	4JJ1-TCC		4JJ1-TC	
Type	4-Cylinder Inline, 4 Cycle, Water-Cooled			
	OHV, Turbo with Intercooler		DOHC, VGS Turbo with Intercooler	
Displacement	cc			
Maximum Output (Gross)	77 (105) @ 3,200		91 (125) @ 2,600	
Maximum Torque	230 @ 1,400-3,400		354 @ 1,500	
Emission Level	Euro 4			
Fuel System	Commonrail Direct Injection			
TRANSMISSION				
Model / No. of Speed	MSB-5S		MYY-5M	
Gear Ratio	Manual 5-Speed			
	1st	5.016		5.315
	2nd	2.672		2.908
	3rd	1.585		1.655
	4th	1.000		1.000
	5th	0.770		0.721
	Reverse	4.783		5.068
	Final	5.857		4.556
WEIGHT & CAPACITIES				
Gross Vehicle Weight	kg	4,800		5,100
Curb Weight	kg	1,920	1,970	2,015
				2,065
Front	kg	1,385	1,395	1,465
Rear	kg	535	575	550
				590
Fuel Tank Capacity	l	75	100	75
				100
AXLE				
Front	Type	Reverse Elliot, I-Beam		
Front Axle Capacity (Design)	kg	2,900		
Rear	Type	Banjo, Full Floating		
Rear Axle Capacity (Design)	kg	3,600		4,600
SUSPENSION SYSTEM				
Suspension	Front	Semi Elliptical Alloy Steel Leaf Spring with Double Acting Telescopic Shock Absorber, Stabiliser Bar		
	Rear	Semi Elliptical Alloy Steel Leaf Spring with Double Acting Telescopic Shock Absorber		
TYRES & WHEELS				
Tyres	205/85R16		205/75R17.5	
Wheels	16 x 5.5J-85		17.5 x 5.25-115	
BRAKES				
Service	Type	Hydraulic System with Auto Adjusting Front and Rear Drum Brakes		
		Dual Circuit, Vacuum Assistance and Anti-Lock Brake System (ABS) with Electronic Brake Force Distribution (EBD)		
Parking Brake Type	Transmission Mounted, Mechanical Operated Internal Expanding			
Auxiliary	Exhaust Brake			
STEERING				
Steering System	Power Assist, Recirculating Ball Type			
Min. Turning Radius	m	5.1	7.3	5.6
				7.3
ELECTRICAL				
Battery	95D31L x 1		80D26L x 2	
Alternator	12V-60A		24V-90A	
OTHER SAFETY				
Safety	Supplemental Restraint System (SRS) with Pre-Tensioner Seatbelt			
	Anti-Slip Regulator (ASR) with On/Off Function			
	Cab Tilt Warning			
Security	Central Locking with Remote Keyless Entry		Central Locking with Remote Keyless Entry & Immobiliser	
DIMENSION				
Overall Length	mm	4,730	6,025	4,730
Overall Width	mm		1,815	
Overall Height	mm	2,172	2,175	2,172
Wheelbase	mm	2,475	3,345	2,475
				3,345
Front Overhang	mm		1,110	
Rear Overhang	mm	1,145	1,570	1,145
Front Tread	mm		1,475	
Rear Tread	mm			1,445
Cab to Axle Center	mm	2,022	2,892	2,022
				2,892

ISUZU

ISUZU MALAYSIA SDN BHD 200401026438 (664846-H)

501D, LEVEL 5, TOWER D, UPTOWN 5, NO.5, JALAN SS21/39,
DAMANSARA UPTOWN, 47400 PETALING JAYA, SELANGOR DARUL EHSAN.
GENERAL LINE: 03-7723 9777 FAX: 03-7723 9779
HOTLINE: 1-300-88-1133 www.isuzu.net.my

[f](#) IsuzuTrucksMalaysia [y](#) IsuzuTrucksMalaysia [globe](#) www.isuzu.net.my

ISUZU SERVICE CENTRE SDN BHD 201601034731 (1205672-X)

LOT 730, JALAN SG. RASAU, SECTION 16,
40200 SHAH ALAM, SELANGOR DARUL EHSAN.
PHONE: 03-5513 0518
FAX: 03-5512 7550

TESTED AND PROVEN POWERTRAIN



NLR PRO

4JJ1-TCC


Displacement: 2,999cc

Max. Output (Gross): 77kW (105ps) @ 3,200rpm

Max. Torque: 230Nm @ 1,400 - 3,400rpm

105PS
Max Power

230Nm
Flat Torque



NMR 125

4JJ1-TC

Displacement: 2,999cc




Max. Output (Gross): 91kW (125ps) @ 2,600rpm

Max. Torque: 354Nm @ 1,500rpm

125PS
Max Power

354Nm
Flat Torque

CLASS-LEADING SAFETY AND LONG TERM COST SAVINGS



ASR traction control helps prevent wheelspins and improves vehicle stability when driving on slippery roads.

EBD is a function that uses the ABS to distribute braking force between the front and rear wheels to compensate for changes in the load conditions or any shift of load due to acceleration/deceleration, thus preventing premature locking of the rear wheels.




*SRS airbag system and seat belt with pretensioner are activated in the event of a frontal collision, mitigating impact to the head and chest.

*Applicable for driver only.



Brand New Feature - USB Port



Cabin Tilt Warning & Buzzer for driver safety warning



LED Headlight to provide better visibility



Gross Vehicle Weight (GVW) from 4.8T increased to 5.1T

Dealer's information

ISUZU
GENUINE PARTS

ISUZU
BEST VALUE PARTS